

注塑用机械手 TAKE-OUT ROBOT

EUW-80II
EUW-80sII



Injection Press. Range

100 ~ 220ton

标准功能 STANDARD FUNCTION

- Packaging motion: Max. 25x points
- First packaging motion: 115 x 2
- Forward and reverse at removing side
- Position control during traverse
- Position midway descent at release side
- Ejector link
- Defective product reject circuit
- Initial defective product reject circuit
- Delayed arm descent
- Midway summit release: Move / Restart
- Runner release within mold
- Additional vacuum sucking unit: 2 circuit
- Delayed traverse
- Undercut reject circuit
- Overpressure

型式 MODEL

单位 UNIT EUW-80II EUW-80sII

型式 MODEL	单位 UNIT	EUW-80II	EUW-80sII
最大取件重量	kg	25	25
最大取件速度	m/min	115	115
最大行程	m	1.5	1.5
最大取件重量	kg	25	25
最大取件速度	m/min	115	115
最大行程	m	1.5	1.5
最大取件重量	kg	25	25
最大取件速度	m/min	115	115
最大行程	m	1.5	1.5

0.49MPa Air Cylinder Driving Force (Air Pressure at 0.49MPa)

Stroke

[The main body of the page contains a large, faint watermark or bleed-through from the reverse side of the paper. The text is illegible due to its low contrast and orientation.]

